

ACE



Features:

ACE is outdoor wall mounted bulkhead, made of PC housing, PC frosted cover with stainless steel screw, Anti-yellowing properties.

This type of light fixtures are often designed to be weather-resistant, ensuring durability and functionality in various environmental conditions.

They utilize energy-efficient LED technology, offering longevity, low heat emission, and a variety of color options.

They serve both functional and aesthetic purposes, enhancing safety while contributing to the overall design of a space.

It is use for a specific application, it's essential to consider factors such as the level of illumination needed, the design aesthetic of the space, and any applicable safety regulations.

Technical Specifications:

Input Voltage : 220- 240 VAC, 50 Hz.

Wattage : 8-20W

High Lumen : 75lm/W

4 STEP Mac Adam

Isolated driver, surge protection 2KV

Lamp Type : SMD

Operating Temperature: -20°C to 50°C

Glow Wire Test 850° C

Warranty : 5 Years

Life Time : 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Boundary Wall

Balcony

Roof

Shaft

Corridors

Installation Method:

Surface and Ceiling mounted.

Wattage(W)	:	8	12	15	20
Finish	:	White(W)	Black(B)	Grey (G)	
Kelvin*	:	3000K	4000K	6500K	
Beam Angle	:	120°			
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming

*Special Color and Finish on request


Product Code (540135):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
8	600LM	135x220
12	900LM	135x220
15	1,125LM	135x220
20	1,500LM	135x220

*Luminous øux value is calculated for 4000K CRI>80

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 540135 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	B-Black
65K - 6500K		3 - DALI	G-Grey	
			4 - Phase Dimming	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C