


ALKA



Features:

ALKA is the series of outdoor wall surface mounted light with modern design, die cast aluminum Body , Anti Yellowing PC diffuser.
Simple Installation.
Perfect design for the very good light emittance.
Homogenous light distribution.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.
Wattage: 24W
High Lumen: 40lm/w
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: SMD
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at ta 25°C
(L80/B10)

Fields of Application:

Roof Parapet
Corridors
Balcony
Compound wall

Installation Method:

Wall Mounted.

Wattage(W)	:	24				
Finish	:	Gray(G)				
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	120°				
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	


*Special Color & Finish on request

Product Code (54030024):

Wattage	Lumens(lm)	Dimension(LxWx H) mm
24	960LM	300x100x140

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Standards

- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 54030024 27K 120D 8 1 G

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	120D - 120°	8->80	1 - ON/OFF	G-Gray
30K - 3000K		9->90	2 - 0/1-10V	
40K - 4000K			3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C