


## AMAZ



### Description:

AMAZ is IP68 light, highly durable and versatile lighting devices with an Ingress Protection (IP) rating of 68. This rating signifies complete protection against dust and allows the lights to be submerged in water beyond 1 meter.

It comes with different CCT , RGB LED sources and various beam angles this family is a perfect solution to the requirement.

Ideal for challenging environments, IP68 lights are resilient, making them suitable for outdoor, marine, and demanding applications, ensuring reliable performance in harsh conditions.

### Product Specifications:

Housing : Stainless steel 316 SUS  
 Front cover : Stainless steel 316 SUS  
 Glass : Silver print glass  
 Gasket: Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface Mounted  
 Adjustable: Yes

### Technical Specifications:

Wattage: 6 - 9 W  
 Voltage: DC24V  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: III  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

### Parameter:


Wattage(W)	:	6W / 9W
Finish	:	Stainless Steel 316 (SS)
Kelvin*	:	2700K/ 3000K/ 4000K/ 6000K /RGB
Beam Angle	:	5° / 8° / 15° / 25° / 40° / 60°
CRI	:	80
Control Mode	:	ON/OFF /DALI / 0 / 1-10V / Phase Cut / DMX

### Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
552083	06-6W(3X2W)	27-2700K	D-24VDC	5-5°	SS-Stainless Steel 316	1-ON/OFF
	09-9W(3X3W)	30-3000K		8-8°		2-DALI
		40-4000K		15-15°		3-0/1-10V
		60-6000K		25-25°		4-Phase Cut
		92-RGB		40-40°		5-DMX
		93-RGB DMX		60-60°		

**Ex: Order Code:** 5520830627D'5SS1

### Photometric:



### Standards:

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C