pluxb

IP65 IK10

ANN

LED LM - 80 FLICKER FREE



Description:

ANN is a slim Up-Down decorative wall-mounted LED light fixture with a minimalist design.
The light source is positioned at the downward and upward direction.
It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.
These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.
They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.
It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Reflector : Anodized Aluminium
Light Source: OSRAM / CREE
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mt. power cable
Driver : High efficiency, low flicker driver
Installation Type: Wall mounted
Adjustable: No

Technical Specifications:

Wattage: 6W
Voltage: 220-240VAC, 50-60Hz
Lumen: 67lm/W
Mac Adam: 3 Step
Safety Class: III
Dimension : D40*H600mm
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	6W
Finish	:	Black (B) / White (W) / Bronze (BR) / Copper (CP)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	15° / 24° / 36°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 36° beam angle, 4000K color temperature and CRI 80.

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:


Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540040	06 - 6W (2x3W)	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
		30-3000K		24-24°	W - White	2-DALI
		40-4000K		36-36°	BR - Bronze	
		60-6000K			CP - Copper	


Ex: Order Code: 5400400627A'15B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C







Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C