



APHRO



Description:

APHRO is a Linear Wall Washer lighting fixture designed to be mounted on walls, delivering uniform and aesthetically pleasing illumination across vertical surfaces.

This fixtures typically feature a sleek, linear profile that allows them to seamlessly integrate into architectural façades, corridors, and exterior walls.

Engineered to provide even light distribution, enhancing textures and architectural details while minimizing glare.

Toughened glass surface, with high hardness, not easy to break. It comes with different CCT, RGB LED sources and C5 Marine Grade Coating, this family is a perfect solution to the requirement.

The length can be customized 250mm, 500mm, 750mm, 1.5mtr. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

- Housing : Die cast Aluminum
- Glass : Tempered glass
- Gasket: Molding shaped silicone seal
- Accessory: Side cover
- Lens/Reflector : Optical lens (efficiency>90%)
- Power Cable: 0.5 mt. power cable included
- Driver : High efficiency, low flicker driver
- Installation Type: Surface Mounted

Technical Specifications:

- Wattage: 36 - 48W
- Voltage: DC24V/ AC10V-265V
- Frequency: 50-60Hz
- Light Source: OSRAM/EPISTAR/CREE
- Lumen: 75lm/W
- Mac Adam: 3 Step
- Safety Class: III
- Working Temperature:-25°C to 60°C
- Life Time: 50,000hrs (L80/B10) at 35°C
- Humidity : <95%
- Warranty: 5 Years

Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Parameter:

Wattage(W)	:	36W / 48W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	2700K/ 3000K/ 4000K / 6500K
Beam Angle	:	10°/ 15°/ 30°/ 45°/ 60°/ 20°* 45°/ 15°*60°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / Bluetooth

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5424061	36-36W	27-2700K	D-24VDC	10-10°	B-Black	1-ON/OFF
		30-3000K		15-15°	G-Grey	2-DALI
	40-4000K	30-30°			3-0/1-10V	
	65-6500K	45-45°			4-Phase cut	
		60-60°			5-Bluetooth	
			20*45-20°*45°			

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

15*60 - 15°*60°

Ex: Order Code: 54240613627D'10B1

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5424061	36-36W	27-2700K	A - 10V-265VAC	10-10°	B-Black	1-ON/OFF
	48-48W	30-3000K		15-15°	G-Grey	2-DALI
		40-4000K		30-30°		3-0/1-10V
		65-6500K		45-45°		
				60-60°		
				20*45-20°*45°		
				15*60 - 15°*60°		

Ex: Order Code: 54240613627A'10B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C