



APHRO



Description:

APHRO is a Linear outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination.

These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas. Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions.

Toughened glass surface, with high hardness, not easy to break. It comes with RGB control and various beam angles this family is a perfect solution to the requirement.

The length can be customized 250mm, 500mm, 750mm, 1.5mtr. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.


Product Specifications:

Housing : Die cast Aluminum
Glass : Tempered glass
Gasket: Molding shaped silicone seal
Accessory: Side cover
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted

Technical Specifications:

Wattage: 60 - 80W
Voltage: DC24V/ AC10V-265V
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 50lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 60°C
Life Time: 50,000hrs (L80/B10) at 35°C
Humidity : <95%
Warranty: 5 Years

Photometric:



Parameter:

Wattage(W)	:	60W / 80W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	RGBW/ RGBW DMX
Beam Angle	:	10°/ 15°/ 30°/ 45°/ 60°/ 20°* 45°/ 15°*60°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / DMX

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5494061	60-60W	82-RGBW	D-24VDC	10-10°	B-Black	1-ON/OFF
	80-80W	83-RGBW DMX		15-15°	G-Grey	2-DALI
				30-30°		3-DMX
				45-45°		
				60-60°		
				20*45-20°*45°		
				15*60 - 15°*60°		

Ex: Order Code: 54940616082D*10B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C