




ARIA



Features:

ARIA is Recessed Trimless Spot Light made from die-cast aluminum with a solvent-free powder coating for durability and eco-friendliness.

It features a compact lamp body with high-power output, making it suitable for both low and high ceiling suspension.

A mini small cutout, allowing for a discreet installation. The spotlight also supports different beam angles providing flexibility in light distribution.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.

Wattage: 8W

Efficiency: 110lm/W

High efficiency, low flicker driver

2 STEP / 3 STEP Mac Adam

Lamp Type: COB

Light Source: CREE/ CITIZEN

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Lifetime 50,000hrs at a 25°C(L90/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Museums

Restaurants

Painting Exhibitions

Theaters

Installation Method:

Recessed.

Wattage(W)	:	8				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5700K
Beam Angle	:	20°	30°	40°	50°	
CRI	:	90+				
Driver	:	ON/OFF	DALI	Phase Dimming		





*Special Color and Finish on request

Product Code (96705608.10):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out (mm)
8	880LM	56x72	35

*Luminous flux value is calculated for 4000K CRI>90, 2 STEP / 3 STEP Mac Adam

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96705608.10 27K 20D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	20D - 20°	9-	1 - ON/OFF	W-
30K - 3000K	30D - 30°	>90	2 - DALI	White
35K - 3500K	40D - 40°		3 - Phase	B-
40K - 4000K	50D - 50°		Dimming	Black
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C