



ARMO



Reflector Option -



Features:

ARMO is a recessed downlight, expertly crafted from Die cast aluminum and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear. It features a customized anti-glare reflector that supports multiple beam angles, achieving UGR <19 to ensure visual comfort in compliance with lighting standards. Reflector colour options are available in White, Black, Chrome, and Silver. Homogenous, well-balance light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.
 Wattage: 12-25W
 Efficiency: 90lm/W
 High efficiency, low flicker driver
 3 STEP Mac Adam
 Lamp Type: COB
 Chip Brand : VS / Citizen / CREE
 Operating Temperature: -20°C to 55°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Lifetime : 100,000hrs at a 25°C(L80/B10)

Fields of Application:

Retail
 Education
 Galleries hotels
 Living spaces
 Museums
 Restaurants
 Painting Exhibitions
 Theaters

Installation Method:

Recessed

Wattage(W)	:	12	15	20			
Finish	:	White(W)	Black(B)				
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	5700K
Beam Angle	:	24°	36°	60°			
CRI	:	80+	90+				
Driver	:	ON/OFF	DALI	Phase Dimming 1-10V			


*Special Color and Finish on request

Product Code (98811020):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out (mm)
12	1,080LM	110x75	100
15	1,350LM	110x75	100
20	1,800LM	110x75	100

*Luminous flux value is calculated for 4000K CRI>90,

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 98811020 27K 24D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	24D - 24°	8->80	1 - ON/OFF	W-White
30K - 3000K	36D - 36°	9->90	2 - DALI	B-Black
35K - 3500K	60D - 60°		3 - Phase Dimming	
40K - 4000K			4 - 1-10V	
50K - 5000K				
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C