

ASH



Features:

ASH IP66 high-quality lighting fixture is built with premium materials to ensure durability and performance. The body is crafted from either PMMA or PC material, both known for their excellent transparency and impact resistance, paired with an aluminium reflector inside to enhance light distribution.

Stainless steel end caps add a sleek, modern finish while also providing robust protection against wear and corrosion, ensuring the fixture remains pristine in any environment. The extrusive design delivers superior waterproofing, making it suitable for use in moisture-prone areas or outdoor applications.

*Available options: 1) Emergency lighting (EM kit) 2) Motion sensor.

Technical Specifications:

Input Voltage : 220- 240 VAC, 50-60Hz.
 Wattage : 18-24W
 High Lumen : 150lm/W
 3 STEP Mac Adam
 High efficiency, low Flicker Philips driver
 Lamp Type : Linear Rigid Modules
 Operating Temperature: -20°C to 50°C
 Glow Wire Test 850° C
 Warranty : 5 Years
 Life Time : 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Offices
 Warehouses
 Schools
 Workstations
 Corridors
 Hospitals
 Sheds
 Underground Parking

Installation Method:

Surface/Suspended

Wattage(W)	:	18	24			
Finish	:	Gray(G)				
Kelvin*	:	3000K	4000K	5000K	6000K	6500K
Beam Angle	:	120°				
CRI	:	70+	80+			
Driver	:	ON/OFF	0/1-10V	DALI		

*Special Color & Finish on request


Product Code (960007524):

Wattage	Lumens(LM)	Dimension(LxØ) mm
18	2700LM	600x75
24	3600LM	600x75

*Luminous flux value is calculated for 4000K and CRI>80.

*Above mentioned wattages can be customized according to designed requirement.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 960007524 30K 120D Z 1 G

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	7->70	1 - ON/OFF	G-Gray
40K - 4000K		8->80	2 - 0/1-10V	
50K - 5000K			3 - DALI	
60K - 6000K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C