


AURO



**Features:**

AURO is a recessed adjustable spotlight, expertly crafted from premium aluminum and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear.

The luminaire is simple, can be integrated into almost any room architectural, while its 27° tilt adjustment on one side offers precise directional lighting, enabling focused illumination exactly where it is needed.

Anti-glare reflector options color with White, Black or Chrome.

For enhanced customization, various CRI (Color Rendering Index) and CCT (Correlated Color Temperature) options are available upon request, allowing designers to create the perfect lighting atmosphere.

The product also available with a range of accessories, including a honeycomb louvre for superior glare control, linear spread glass for elongated light distribution, and clear glass for maximum output and clarity. This combination of refined design, advanced optics.

**Technical Specifications:**

Input Voltage: 220- 240 V AC, 50/60Hz.  
 Wattage: 6-10W  
 Efficiency: 85lm/W  
 High efficiency, low flicker driver  
 3 STEP Mac Adam  
 Lamp Type: COB  
 Operating Temperature: -20°C to 45°C  
 Glow Wire Test 850° C  
 Warranty: 5 Years  
 Lifetime 50,000hrs at a 25°C(L90/B10)

**Fields of Application:**

Retail  
 Education  
 Galleries hotels  
 Living spaces  
 Museums  
 Restaurants  
 Painting Exhibitions  
 Theaters


**Installation Method:**

Recessed Adjustable

Wattage(W)	:	6	8	10		
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5700K
Beam Angle	:	15°	22°	33°	47°	55°
CRI	:	90+				
Driver	:	ON/OFF	DALI	Phase Dimming	1-10V	

\*Special Color and Finish on request

**Product Code (96706210.50):**

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out  (mm)
6	510LM	62x92	55
8	680LM	62x92	55
10	850LM	62x92	55

\*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

## Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96706210.50 27K 15D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	9-	1 - ON/OFF	W-
30K - 3000K	22D - 22°	>90	2 - DALI	White
35K - 3500K	33D - 33°		3 - Phase	B-Black
	47D - 47°		Dimming	
40K - 4000K	55D - 55°		4 - 1-10V	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C