

## AXIS



### Features:

Axis Surface Mounted Spotlight is designed to be installed directly on the surface of the ceiling, making them ideal for spaces where recessed installation is not possible.

This mounting style is easy to install and offers a clean, modern look.

Die cast aluminum body Provides durability, strength, and superior heat dissipation, PMMA Lens with a deep baffle for a smooth lighting effect.

Available with different options Beam angle, give you flexibility to customize your lighting for specific tasks, whether it's highlighting artwork or providing ambient lighting.

### Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 2x20W

High Lumen: 120lm/w

3 SDCM / 2 SDCM

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10)

### Fields of Application:

Retail

Education

Galleries hotels

Living spaces

### Installation Method:

Surface Mounted Track.

Wattage(W)	:	2x20				
Finish	:	White(W)	Black(B)	Gray(G)		
Kelvin*	:	2700K	3000K	3500K	4000K	5000K
Beam Angle	:	10°	15°	24°	36°	50°
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


\*Special Color and Finish on request

### Product Code (96828040):

Wattage	Lumens(lm)	Dimension(L x Ø x H) mm
40	4800LM	280x66x135

\*Luminous flux value is calculated for 4000K CRI>80

### Photometric:



## Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: ~~96828040~~ 27K 10D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	10D - 10°	8->80	1 - ON/OFF	W-White
30K - 3000K	15D - 15°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	24D - 24°		3 - DALI	G-Gray
40K - 4000K	36D - 36°		4 - Phase Dimming	
50K - 5000K	50D - 50°		5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C