


## BAIL



### Description:

BAIL is ceiling wall lights can be mounted on ceilings, walls, or any suitable surface, providing Flexibility in installation locations..

The sealed construction of the CEILING light ensures protection against the ingress of dust particles and water, making it ideal for both indoor and outdoor applications.

It suitable for use in environments where exposure to dust and water is a concern.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

Due to their robust construction and weather-resistant features, CEILING wall lights with an IP65 rating are suitable for various applications, including outdoor spaces, bathrooms, corridors, and industrial environments.

### Product Specifications:

Front cover : Die cast Aluminium grey  
Housing : Die cast Aluminium grey  
Diffuser : Tempered Glass  
Gasket: Moulding shaped silicone seal  
Lens/Reflector : Optical lens (efficiency>90%)  
Power Cable: 0.5 mt. power cable included  
Driver : High efficiency, low flicker driver  
Installation Type: Surface mounted  
Adjustable: No

### Technical Specifications:

Wattage: 9W  
Voltage: 220-240VAC  
Frequency: 50-60Hz  
Light Source: OSRAM/EPISTAR/CREE  
Lumen: 100lm/W  
Mac Adam: 3 Step  
Safety Class: II  
Working Temperature:-20°C to 55°C  
Life Time: 50,000hrs (L80/B10) at 35°C  
Warranty: 5 Years

### Parameter:


Wattage(W)	:	9W
Finish	:	Grey (G) /Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	8° / 15° / 25° / 40° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540095	9-9W(9x1W)	27-2700K	A-220-240VAC	8-8°	G-Grey	1-ON/OFF
		30-3000K		15-15°	C-Customized	2-DALI
		40-4000K		25-25°		3-0/1-10V
		60-6000K		40-40°		
				60-60°		

Ex: Order Code: 540095927A'8G1

### Photometric:



### Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C