pluxb

IP40

BAR III 200



End Cap

Accessories:

Surface Mounted Clip

Suspention Kit

Trimless Clip

Features:

BAR III 200 High Quality Bendable Aluminum using the highest standard 6063-T6 aluminum stronger than 6063-T5, and deep anodizing (more than 12µm)of profile protects the aluminum against corrosion, extends durability.
Lighting fixtures can be connected into linear and polygonal lighting lines.
Lens Options: PMMA Matt Diffuser / Micro Prismatic Lens / Prism Lens + Optics Diffusion. sheet, all diffusers and lens are UV stabilized, no inclusions or scratches on the surface.
Standard Length: 570 mm / 1120 mm / 1480 mm / 1750 mm /2100mm
Other lengths can be customized as per design.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.
Wattage: 45-120W/M
Luminaire Efficacy: 120lm/W
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: Linear Rigid Module
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at ta 25˚C
(L80/B10)

Fields of Application:

Retail
Education
Galleries hotels
Living spaces

Installation Method:

Suspended / Surface Mounted

Wattage(W)/M	:	45	50	75	100	120	
Finish	:	White(W)	Black(B)	Silver(S)	Customized(C)		
Kelvin*	:	3000K	4000K	5000K	5700K	6500K	Tunable
Beam Angle	:	120°					
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Bluetooth		

*Special Color & Finish on request

Product Code (96420085120):

Wattage/M	Lumens(LM)	Dimension(WxH) mm	Length(L) mm
45	5400 LM	200x85	990
50	6000 LM	200x85	1200
75	9000 LM	200x85	1480
100	12000 LM	200x85	1970
120	14400 LM	TEXT	2400

*Luminous flux value is calculated for 4000K & CRI>80.
*Above mentioned wattages can be customized according to designed requirement.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Pluxb Lighting d.o.o
Miklavška cesta 75, SI - 2311 Hoce, SLOVENIA
www.pluxb.com

Standards
EN 60598-1
EN 60598-2-2
EN 60598-2-22
EN 60598-3-2
EN 60598-3-3

Order Code Ex: 96420085120 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	B-Black
50K - 5000K			3 - DALI	S-Silver
57K - 5700K			4 - Bluetooth	C-Customized
65K - 6500K				
TuK - Tunable				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C