



BAR III 40



- Optics Diffuser :



- Accessories :



Features:

BAR III 40 High Quality Aluminum using the highest standard 6063-T6 aluminum stronger than 6063-T5, and deep anodizing (more than 12µm) of profile protects the aluminum against corrosion, extends durability.

Lighting fixtures can be connected into linear and polygonal lighting lines.

Lens Options: PMMA Matt Diffuser / Micro Prismatic Lens / Prism Lens + Optics Diffusion. sheet, all diffusers and lens are UV stabilized, no inclusions or scratches on the surface.

Standard Length: 990 mm / 1200 mm / 1480 mm / 1970 mm / 2100mm

Other lengths can be customized as per design.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 20 - 45W/M

Luminaire Efficacy: 120lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: Linear Rigid Module

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C
(L80/B40)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Suspended / Surface Mounted

Wattage(W)/M :	20	30	40	45		
Finish :	White(W)	Black(B)	Silver(S)	Customized(C)		
Kelvin* :	3000K	4000K	5000K	5700K	6500K	Tunable
Beam Angle :	120°					
CRI :	80+	90+				
Driver :	ON/OFF	0/1-10V	DALI	Bluetooth		

*Special Color & Finish on request


Product Code (964407545):

Wattage/M	Lumens(LM)	Dimension(WxH) mm	Length (mm)
20	2400LM	40x75	990
30	3600LM	40x75	1200
40	4800LM	40x75	1480
45	5400LM	40x75	1970

*Luminous flux value is calculated for 4000K & CRI>80.

*Above mentioned wattages can be customized according to designed requirement.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 964407545 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	B-Black
50K - 5000K			3 - DALI	S-Silver
57K - 5700K			4 - Bluetooth	C-Customized
65K - 6500K				
TuK - Tunable				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C