


BAR-G IV 48



Features:

BAR-G IV 48 Linear Grill Extruded Aluminum Profile with highest standard 6063-T6 aluminum, and invisible Screw aluminum endcap, deep anodizing (more than 12μm) that protects against corrosion and extends durability, Matt surface treatment. Opal PMMA and PC Grid with UV stabilized, no inclusions or scratches on the surface. The Lens available with UGR<16. Standard Length with Zagha Linear Modules 570 mm / 1200 mm/ 1480 mm/ 1920mm, tailored length can be manufactured as per design. Homogenous, well-balanced light dispersing with no shadow.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.
Wattage /M: 20 - 60W
Efficacy: 130lm/w
3 STEP Mac Adam
High Efficiency, Low Flicker Driver
LED Modules: W2.5 VS Light & Dark Optics
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at ta 25°C (L90/B10)

Fields of Application:

Retail
Education
Galleries hotels
Living spaces

Installation Method:

Surface Mounted / Suspended.

Wattage(W)	:	20	35	45	60		
Finish	:	White(W)	Black(B)	Silver(S)	Customized		
Kelvin*	:	2700K	3000K	4000K	5000K	5700K	Tunable
Beam Angle	:	65°	90°				
CRI	:	80+	90+	Tunable			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	

*Special Color and Finish on request

Product Code (964487560):



Wattage	Lumens(lm)	Dimension(W XH) mm	Length (L) mm
20	2600 LM	48x75	990
35	4550 LM	48x75	1200
45	5850 LM	48x75	1480
60	7800 LM	48x75	1970

*Luminous flux value is calculated for 4000K CRI>80

* Length and Wattage can be customized as per design

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 964487560 27K 65D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	65D - 65°	8->80	1 - ON/OFF	W-White
30K - 3000K	90D - 90°	9->90	2 - 0/1-10V	B-Black
40K - 4000K		T->Tunable	3 - DALI	S-Silver
50K - 5000K			4 - Phase Dimming	C-Customized
57K - 5700K			5 - Bluetooth	
TuK - Tunable				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C