


## BAZO



### Features:

BAZO Recessed spotlight body made of Die cast aluminum with PMMA Lens and reflector. Hidden deep tube design, fully equipped with different colors of electrostatic process electroplating reflectors.

The product has standard model with UGR<19, available with pinball model with no light leakage, while tilting there is no light Leakage from the corner.

Low glare, glare can be controlled and less than 17.

Dark Optics with high efficiency, Moony Optics ideal for Tunable White Solution.

High light Transmissivity.

### Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 7- 12W

High Lumen: 105lm/w

2 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10)

### Fields of Application:

- Retail
- Education
- Galleries hotels
- Living spaces

### Installation Method:

Recessed Adjustable/ Fixed

Wattage(W)	:	7	10	12			
Finish	:	White(W)	Black(B)	Gray(G)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K	6500K
Beam Angle	:	15°	24°	36°	60°		
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Bluetooth	Phase Dimming	


\*Special Color & Finish on request

### Product Code (96708212.50):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out (mm)
7	735LM	82x92	75
10	1050LM	82x92	75
12	1260LM	82x92	75

\*Luminous flux value is calculated for 4000K CRI>80

### Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

## Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96708212.50 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	36D - 36°		3 - DALI	G-Gray
50K - 5000K	60D - 60°		4 - Bluetooth	
57K - 5700K			5 - Phase Dimming	
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C