



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Reflector :



Features:

Bazo is an adjustable recessed spotlight featuring a premium die-cast aluminum housing, high-transmittance TIR PC optical lens, and high-efficiency optics for superior visual comfort, uniform illumination, and excellent light transmission.

The adjustable head enables precise beam aiming, making it ideal for accent lighting, architectural applications, retail displays, and exhibitions.

The spring clip mounting system ensures quick installation and easy maintenance.

Its precision optical design delivers excellent beam control with $UGR < 14$ for outstanding anti-glare performance. Multiple optical accessories are available, including Honeycomb Anti-Glare Net, Stretch Lens, One-Side Asymmetric Lens, Double-Side Asymmetric Lens, Round Acrylic Ambient Diffuser, Small Round Aperture, Elliptical Aperture, and Polarized Reflector Cup for wall washing, providing flexible lighting effects for various applications. Equipped with high-quality branded lenses, it delivers soft, comfortable, and highly efficient illumination.

Bezels, inner rings, and reflectors can be freely combined and are available in premium PC or die-cast aluminum, with reflector finishes in Matte White, Matte Black, Chrome, Bright Silver, Gold, and Gun Black to suit diverse interior designs.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 7-10W

High Lumen: 75lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Chip Brand: CREE / Bridgelux

Driver Brand: VS / Philips / Eaglerise

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10).

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

kitchens

Vanity & Mirror Lighting

Installation Method:

Recessed Adjustable.

Wattage(W)	:	7	10				
Finish	:	White(W)	Black(B)	Silver(S)	Golden(G)	Chrome(C)	
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	5700K
		6500K	Tunable White				
Beam Angle	:	10°	15°	24°	36°	50°	
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Casambi		





*Special Color & Finish on request

Product Code (99706510.50):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out (mm)
7	525LM	65x80	55
10	750LM	65x80	55

*Luminous flux value is calculated for 3000K CRI>90, 3 STEP Mac Adam.

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 99706510.50 27K 10D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	10D - 10°	8->80	1 - ON/OFF	W-White
30K - 3000K	15D - 15°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	24D - 24°		3 - DALI	S-Silver
40K - 4000K	36D - 36°		4 - Casambi	G-Golden
50K - 5000K	50D - 50°			C-Chrome
57K - 5700K				
65K - 6500K				
TuK - Tunable White				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C