


BIT



Description:

BIT is up-down wall light fixture designed to illuminate both upward and downward directions. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.

These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Front cover : Die cast Aluminum
Housing : Die cast Aluminum
Glass : Clear glass
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Mounted
Adjustable: No

Technical Specifications:

Wattage: 2 x 5W
Voltage: DC24V / 220-240VAC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: III / II
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:


Wattage(W)	:	2 x 5W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	8° / 15° / 25° / 40° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / DMX

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540039	2x5 - 2x5W	27-2700K	A-220-240VAC	8-8°	G-Grey	1-ON/OFF
		30-3000K		15-15°	B-Black	2-DALI
		40-4000K		25-25°	W-White	3-0/1-10V
		60-6000K		40-40°	C-Customized	5-DMX
				60-60°		

Ex: Order Code: 5400392x527A'8G1

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3