


BRIZ



Description:

BRIZ is wall down light fixture designed to illuminate downward directions. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect. These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces. They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications. It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Front cover : Die cast Aluminium grey
 Housing : Die cast Aluminium grey
 Diffuser : Clear Glass
 Gasket: Moulding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface mounted
 Adjustable: Yes

Technical Specifications:

Wattage: 1.5-2W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:


| | | |
|--------------|---|---------------------------------------|
| Wattage(W) | : | 1.5W / 2W |
| Finish | : | Grey (G) /Customized (C) |
| Kelvin* | : | 2700K/ 3000K / 4000K / 6000K |
| Beam Angle | : | 8° / 15° / 25° / 40° / 60° |
| CRI | : | 80 |
| Control Mode | : | ON/OFF / DALI / 0 / 1-10V / Phase Cut |

Order Code:

| Product Code | Wattage | CCT | Voltage | Beam Angle | Finish | Control Mode |
|--------------|-----------------|----------|--------------|------------|--------------|--------------|
| 540061 | 01-1.5W(1x1.5W) | 27-2700K | A-220-240VAC | 8-8° | G-Grey | 1-ON/OFF |
| | 02-2W(1X2W) | 30-3000K | | 15-15° | C-Customized | 2-DALI |
| | | 40-4000K | | 25-25° | | 3-0/1-10V |
| | | 60-6000K | | 40-40° | | 4-Phase cut |
| | | | | 60-60° | | |

Ex: Order Code: 5400610127A'8G1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C