



BRUNO



Features:

BRUNO is an Adjustable Downlight has a sleek and versatile recessed lighting. Crafted from durable die cast Aluminum this fixture ensures longevity, superior heat dissipation, Its sleek design is engineered for precision and adaptability, featuring a 50° and 355° rotation, allowing for precise light direction. Available in six sophisticated body colors—Black, White, Matt Silver, Matt Brass, Nickel, and Chrome.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.
Wattage: 6W
High Lumen: 90lm/w
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: COB
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at 25°C (L80/B10).

Fields of Application:

Retail
Galleries hotels
Living spaces
Conference rooms
Counters
Restaurants


Installation Method:

Recessed Adjustable

Wattage	:	6					
Finish	:	White(W)	Black(B)	Silver(S)	Brass(B)	Nickel(N)	Chrome(C)
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	
Beam Angle	:	15°	24°	36°	60°		
CRI	:	90+					
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	


*Special Color & Finish on request

Product Code (96806506.60):

Wattage	Lumens(lm)	Dimension(LxWxH)m	Cut Out  (mm)
6	540LM	65x65x44	55x55

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96806506.60 27K 15D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	9->90	1 - ON/OFF	W-White
30K - 3000K	24D - 24°		2 - 0/1-10V	B-Black
35K - 3500K	36D - 36°		3 - DALI	S-Silver
40K - 4000K	60D - 60°		4 - Phase Dimming	B-Brass
50K - 5000K			5 - Bluetooth	N-Nickel
				C-Chrome

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C