
pluxb

IP65 IK08

CACEY

LED LM - 80 FLICKER FREE





Description:

CACEY is a outdoor recessed wall light features a compact and minimalist design, ideal for subtle architectural illumination. Available in aluminium, brass, or stainless steel construction, it offers durability and versatile design options.
Finish options include Textured White, Textured Black, Corten, Brushed Varnish, Light Bronze, Dark Bronze, Polished SUS316, and Brushed Bronze.
Optional IP44 and IP65 ratings are available to suit different installation requirements.
Available in black and white finishes to complement different architectural styles.
Its sleek appearance blends seamlessly with modern outdoor spaces. Designed for recessed installation, it provides effective lighting for staircases, pathways, and walls.

Product Specifications:

Front cover: Aluminum / Brass / Stainless Steel
Housing : Die cast aluminium
Coating : Powder Coating
Diffuser : Tempered Glass
Light Source: Osram
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 2 - 3W
Voltage: 24VDC
Frequency: 50-60Hz
Lumen: 55lm/W
Mac Adam: 3 Step
Safety Class: III
Cut out : L70xW70xH50mm
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	2W / 3W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	60°
CRI	:	90+ 97+
Control Mode	:	ON/OFF / DALI

Standard :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539086	02-2W 03-3W	27-2700K 30-3000K 40-4000K 60-6000K	D - 24VDC	60-60°	G- Grey B-Black W-White C-Customized	1-ON/OFF 2-DALI

Ex: Order Code: 5390860227D'60G1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C