


CALO



Features:

Recessed Downlight are designed with simple and easy appearance, in line with contemporary aesthetic concept.

Die Cast Aluminum body with solvent free power coated.

Antiglare reflector with excellent light dispersion

High thermal conductivity double-sided aluminum substrate.

High light Transmissivity.

Homogenous, well-balanced, no shadow

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 20-25W

High Lumen: 110lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces


Installation Method:

Recessed.

Wattage(W)	:	20	25			
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	100°				
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


*Special Color and Finish on request

Product Code (96823825):

Wattage	Lumens(lm)	Dimension(Ø) mm	Cut Out  (mm)
20	2200LM	238	226
25	2750LM	238	226

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96823825 27K 100D 8 1 W				
CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	100D - 100°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Bluetooth	