


CHIO



Features:

CHIO sleek design, durability, and high-performance surface.

Die cast aluminum body with recessed adjustable Downlight design, with high-quality PC diffuser, renowned for its superior optical clarity.

Having different beam angles allows for flexibility in lighting design to minimize glare and ensure uniform light distribution Interchangeable and add-on glass diffuser or honeycomb louvre.

45° tiltable light focus make this fitting good for ambient lighting.

UGR <19 this spotlight sets a new standard in visual comfort.

Where innovation meets elegance to illuminate spaces with unparalleled brilliance and comfort.

Technical Specifications:

Input Voltage : 220- 240 V AC,
50/60Hz.

Wattage : 8-10W

High Lumen : 100lm/w

Light source: Citizen CLU02Q-1202

2 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type : COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty : 5 Years

Life Time : 50,000hrs at ta 25°C

(L90/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces


Installation Method:

Recessed Adjustable

Wattage(W)	:	8	10		
Finish	:	White(W)	Black(B)	Brushed Varnish	Light Bronze Dark Bronze
Kelvin*	:	2700K	3000K	4000K	
Beam Angle	:	15°	24°	38°	
CRI	:	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming Bluetooth




*Special Color and Finish on request

Product Code (96704010.50):

Wattage	Lumens(lm)	Dimension(Ø H) mm	Cut Out  (mm)
8	800LM	40x90	82
10	1000LM	40x90	82

*Luminous lux value is calculated for 4000K CRI>90

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96704010.50 27K 15D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	9->90	1 - ON/OFF	W-White
30K - 3000K	24D - 24°		2 - 0/1-10V	B-Black
40K - 4000K	38D - 38°		3 - DALI	B-Brushed Varnish
			4 - Phase Dimming	L-Light Bronze
			5 - Bluetooth	D-Dark Bronze

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C