











CHRYS





















Description:

CHRYS is a modern decorative wall-mounted LED light fixture with a minimalist design. The light source is positioned at the downward and upward direction.

It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.

These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Housing: Die cast Aluminium grey

Diffuser: Tempered Glass Reflector: Anodized Aluminium

Gasket: Moulding shaped silicone seal Power Cable: 0.5 mt. power cable Driver: High efficiency, low flicker driver

Installation Type: Wall mounted

Adjustable: No

Technical Specifications:

Wattage: 6W

Voltage: 85-265VAC, 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 100lm/W Mac Adam: 3 Step Safety Class: II

Working Temperature: -20°C to 55°C Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years

Parameter:

Wattage(W) 2X3W

Finish : Grey (G) /Customized (C)


2700K/3000K/4000K/6000K Kelvin*

Beam Angle 120°

CRI 80

Control Mode : ON/OFF / DALI / 0 / 1-10V

Photometric:



Standards:

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540200	06-2X3W	27-2700K	A-220-240VAC	120-120°	G-Grey	1-ON/OFF
		30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				

Ex: Order Code: 5402000627A'120G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C