
pluxb

IP65 IK08

CICA

LED LM - 80 FLICKER FREE





Description:

CICA is a series of high-quality Spike Light, bionic design, rich textured design composed of die-casting aluminum parts, reflector, tempered glass.
High-quality outdoor Powder coating spraying process, Cica have Tough weather resistance and protection grade is IP65.
Die-casting molding process, good heat dissipation performance. Deep anti-glare reflector design, clean light spot, with good anti-glare effect.
Easy installation, angle adjustable from two directions which can precisely meet the lighting needs of lighting trees, architecture and sculpture.

Product Specifications:

Housing : Die cast aluminium
Coating: Powder Coating
Diffuser : Tempered glass
Net Weight : 0.33KG
Gasket : Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable: Yes

Technical Specifications:

Wattage: 5W
Voltage: AC220-240V
Frequency: 50-60Hz
Light Source: CREE XPE2
Lumen: 65lm/W
Mac Adam: 3 Step
Safety Class: III / II
Working Temperature:-25°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	5W
Finish	:	Silver (S) / Black (B) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	24° / 36°
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI

Standards

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:


Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
541050	05-5W	27-2700K 30-3000K 40- 4000K 60-6000K	A - 220 - 240VAC	24 - 24° 36 - 36°	S- Silver B-Black C-Customized	1-ON/OFF 2-DALI

Ex: Order Code: 5410500527A'24S1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C





Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C