


CLAM'O



Description:

CLAM'O is a Walk over pathway light typically feature glass cover, durable, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade.

3mm Toughened safety glass for drive over application up to 5000KG Static Load.

It comes with different CCT , R/G/B LED sources and various beam angles this family is a perfect solution to the requirement.

It has very wide application like For landscape lighting, garden lighting, horticultural engineering design, public fountain square Lighting.

Product Specifications:

Housing : Die cast Aluminum
 Glass : 3mm tempered glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Inground
 Adjustable: No

Technical Specifications:

Wattage: 2 - 3W
 Voltage: DC24V / 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 25lm/W
 Mac Adam: 3 Step
 Safety Class: III / II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	2W / 3W
Finish	:	Black (B)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	Diffused
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V


Text Here...

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
544053	02-2W	27-2700K	D-24VDC	D-Diffused	B-Black	1-ON/OFF
	03-3W	30-3000K				2-DALI
		40-4000K				3-0/1-10V
		60-6000K				
		92-RGB				
93-RGB DMX						

Ex: Order Code: 5440530227D'DB1

Photometric:



Standards

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
544053	02-2W	27-2700K 30-3000K 40-4000K 60-6000K	A-220-240VAC	D- Diffused	B-Black	1-ON/OFF 2-DALI 3-0/1-10V

Ex: Order Code: 5440530227A'DB1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C