



#### CLAY







Wall Wash



#### Standard:

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

# A\*\* | LED | ₹ | @ | & | @ | △ | LM-80 | @ | ✔ |

















CLAY is a High Power LED Inground light which gives Wall Washer Effect. The light body uses the design of increasing heat dissipation space, the burial barrel adopts aluminium alloy compression moulding forming. Surface with anodizing treatment has the stronger structure and Anti-corrosion capability.

Stainless steel faceplate, high pressure die casting light body, surface with electrostatic plastic coating. Lamshade adopts high strength toughened glass, resist the impact and

It comes with different CCT and various beam angles this family is a perfect solution to the requirement. It also comes with Honeycomb Grill and Anti-slip Glass as an option. It has very wide application like For landscape lighting, garden lighting, horticultural engineering design, public fountain square Lighting.

## **Product Specifications:**

Front cover: Stainless Steel 316 Housing: Die cast aluminum grey

Coating: Powder Coating Glass: Tempered glass

Gasket: Molding shaped silicone seal

Lens/Reflector: Optical lens (efficiency>90%) Power Cable: 0.5 mt. power cable included Driver: High efficiency, low flicker driver

Installation Type: Inground

Adjustable: Yes

# **Technical Specifications:**

Wattage: 6W Voltage: 24VDC Frequency: 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 50lm/W Mac Adam: 3 Step Safety Class: III

Working Temperature: -20°C to 55°C Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years

### Parameter:

Wattage(W) 6W

Finish Black (B) / White (W) / Gray (G)

Kelvin\* RGBW / RGBW DMX

Beam Angle 15°/20°/30°/45°/15x60°

CRI **80+** 

ON/OFF / DMX Control Mode

#### Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
544063	6 - 6W	82 - RGBW	D - 24VDC	15 - 15°	B - Black	1-ON/OFF
		83 - RGBW DMX		20-20°	W - White	2-DMX
				30 - 30°	G - Gray	
				45 - 45°		
				15x60 - 15x60°		

Ex: Order Code: 544063682D'15B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C