



CLOG



Description:

CLOG is a modern decorative wall-mounted LED light fixture with a minimalist, rectangular design. The light source is positioned at the downward and upward direction. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.

These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : PMMA Optics
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mt. power cable
Driver : High efficiency, low flicker driver
Installation Type: Wall Mounted
Adjustable: No
Warranty: 5 Years

Technical Specifications:

Wattage: 6W
Voltage: 85-265VAC, 50-60Hz
Light Source: OSRAM/ EPISTAR/ CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: II
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:


Wattage(W)	:	2x3W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540100	06-6W(2x3W)	27-2700K	A-220-240VAC	120-120°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	3-0/1-10V
		60-6000K			C-Customized	

Ex: Order Code: 5401000627A120G1

Photometric:



Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C