































# Features:

COIN is recessed spotlight, with die cast aluminum body and lens. Excellent heat dissipation, long product life and effectively reduce light ageing. The light source is deeply hidden, anti-glare eye protection.

### **Technical Specifications:**

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 1 W

High Lumen: 115lm/w 3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10)

### Fields of Aplication:

Retail

Galleries hotels Living spaces Conference rooms

Counters Restaurants

## **Installation Method:**

Recessed

Wattage(W)	:	1					
Finish	:	White(W)	Black(B)				
Kelvin*	:	2700K	3000K	4000K	5000K		
Beam Angle	:	15°	24°	36°	60°		
CRI	:	<b>80</b> +	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	


\*Special Color & Finish on request


## Product Code (96702801):


Wattage	Lumens(Lm)	Dimension(ØxH) mm	Cut Out₫ ⊃mm
1	115LM	28x27	25


<sup>\*</sup>Luminous øux value is calculated for 4000K CRI>80

#### **Photometric:**









Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96702801 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	36D - 36°		3 - DALI	
50K - 5000K	60D - 60°		4 - Phase Dimming	
			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C