



CORAL



Description:

CORAL is IP65-rated Window light is designed for durability and elegance, making it suitable for various environments. With a zero-glare design, it ensures uniform illumination without any light leakage, even when standing directly in front of it.

Tempered glass cover offers superior scratch and impact protection.

The integrated aluminum alloy housing provides excellent heat dissipation, keeping the LED heat sink surface less than 5°C above ambient temperature. Its sleek and modern design seamlessly blends with any interior while delivering flicker-free and energy-efficient lighting for a comfortable and visually appealing experience.

Product Specifications:

Housing : Die cast Aluminum
Glass : Tempered glass
Coating : Powder Coating
Light Source: Osram / Cree
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable : No

Technical Specifications:

Wattage: 5W
Voltage: DC24V
Frequency: 50-60Hz
Lumen: Single Color (3000K) - 68lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 50°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	5W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	1700K/ 2200K/ 2700K/ 3000K/ 4000K/ 6000K / 6500K
Beam Angle	:	5*110°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 5*110° beam angle, 4000K color temperature and CRI 80.

Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Order Code:


Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
555100	05 - 5W	17-1700K 22-2200K 27-2700K 30-3000K 40-4000K 60-6000K 65 - 6500K	D-24VDC	5*110-5*110°	B - Black G - Grey	1-ON/OFF 2-DALI

5551000517D'5*110B

Ex: Order Code: 1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C