


COZY 14



Features:

COZY 14 High Quality Aluminum using the highest standard 6063-T6 aluminum stronger than 6063-T5, and with deep anodizing of profile protects the aluminum against corrosion, extends durability.

Opal PMMA diffuser helps to soften and distribute light evenly across the surface, reducing harsh shadows and glare, UV stabilized, no inclusions or scratches on the surface.

Idea for standard-width LED strips, ensuring a snug fit and optimal light output, easy access to LED strips for maintenance or replacement.

Standard length 1mtr, 2mtr, 3mtr.

Other lengths can be customized as per design.

Technical Specifications:

Wattage: 5-20W/M

Operating Temperature: -20°C to 45°C

Warranty: 5 Years

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Surface Mounted.

Wattage(W)/M :	5	10	15	20		
Finish :	White(W)	Black(B)	Silver(S)	Customized(C)		
Kelvin* :	3000K	4000K	5000K	5700K	6500K	Tunable
Beam Angle :	120°					
CRI :	80+	90+				
Driver :	ON/OFF	0/1-10V	DALI	Bluetooth		

*Special Color and Finish on request


Product Code (914140920.75):

Wattage/M	Lumens(LM)	Dimension(WxH) mm	Length(mm)
5	350LM	14x09	1000
10	700LM	14x09	1000
15	1050LM	14x09	1000
20	1400LM	14x09	1000

*Luminous flux value is calculated for 4000K and CRI>90 tested with pluxb COB and SMD IP 20 Strip Light.

*Above mentioned wattages can be customized according to designed requirement.

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 914140920.75 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	B-Black
50K - 5000K			3 - DALI	S-Silver
57K - 5700K			4 - Bluetooth	C-Customized
65K - 6500K				
TuK - Tunable				