


## CUBE



### Description:

CUBE is an outdoor up and down wall lamp with special optical design. The design is simple and rich in texture. It is composed of die-casting aluminum, polarized lens and tempered glass. The high-quality outdoor special powder coating process is adopted to make the lamp have strong weather resistance and anti-aging function.

The lamp adopts two polarized lens modules, large-angle polarized lens and wall-washing lens, which are anti-glare and have a large shielding angle.

There are three light distribution modes of direct light, direct light + indirect light, and indirect light to choose from, which can meet the needs of various scenes.

The lamp is suitable for indoor and outdoor facade lighting architectural decorative lighting, etc.

### Product Specifications:

Housing : Die cast Aluminium grey  
 Glass : Tempered Glass  
 Diffuser : Clear Glass  
 Gasket: Moulding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface mounted  
 Adjustable: No

### Technical Specifications:

Wattage: 6-24W  
 Voltage: 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 90lm/W  
 Mac Adam: 3 Step  
 Safety Class: II  
 Working Temperature: -20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

### Parameter:


Wattage(W)	: 6W / 12W / 24W
Finish	: Black (B) / Grey (G) / White (W) / Silver (S) / Customized (C)
Kelvin*	: 2700K / 3000K / 4000K / 6000K
Beam Angle	: 8° / 15° / 25° / 40° / 60° / Asymmetric
CRI	: 80
Control Mode	: ON/OFF / DALI / 0 / 1-10V

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540122	06-6W (2x3W)	27-2700K	A-220-240VAC	8-8°	B-Black	1-ON/OFF
	12-12W (2x6W)	30-3000K		15-15°	G-Grey	2-DALI
	24-24W (2x12W)	40-4000K		25-25°	W-White	3-0/1-10V
		60-6000K		40-40°	S-Silver	
				60-60°	C-Customized	
				AS-Asymmetric		

**Ex: Order Code: 5401220627A8B1**

### Photometric:



### Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C