


DAFFOD'R



Description:

DAFFOD'R is a modern decorative wall-mounted LED light fixture with a oval design. The light has a frosted or opaque diffuser , which softens the light it emits.

This wall light with an outer ring that glows, while the center part remains non-transparent and dark, is a unique design.

The outer ring emits light, creating a halo effect, The center part is opaque, creating a "donut" shape of light.

This type of light fixtures are often designed to be weather-resistant, ensuring durability and functionality in various environmental conditions.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : PMMA Optics
 Gasket: Moulding shaped silicone seal
 Power Cable: 0.5 mt. power cable
 Driver : High efficiency, low flicker driver
 Installation Type: Wall Mounted
 Adjustable: No
 Warranty: 5 Years

Technical Specifications:

Wattage: 18-20W
 Voltage: 85-265VAC, 50-60Hz
 Light Source: OSRAM/ EPISTAR/ CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: III / II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:


| | | |
|--------------|---|---|
| Wattage(W) | : | 18W / 20W |
| Finish | : | Grey (G) / Black (B) / White (W) / Customized (C) |
| Kelvin* | : | 2700K/ 3000K / 4000K / 6000K |
| Beam Angle | : | 120° |
| CRI | : | 80 |
| Control Mode | : | ON/OFF / DALI / 0 / 1-10V / Phase Cut |

Order Code:

| Product Code | Wattage | CCT | Voltage | Beam Angle | Finish | Control Mode |
|--------------|---------|----------|--------------|------------|--------------|--------------|
| 540200 | 18-18W | 27-2700K | A-220-240VAC | 120-120° | G-Grey | 1-ON/OFF |
| 540270 | 20-20W | 30-3000K | | | B-Black | 2-DALI |
| | | 40-4000K | | | W-White | 3-0/1-10V |
| | | 60-6000K | | | C-Customized | 4-Phase cut |

Ex: Order Code: 5402001827A120G1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C