
pluxb

IP65 IK08

DARCY

LED LM - 80 FLICKER FREE





Description:

DARCY is a wall recessed step light is designed to provide subtle, glare-free illumination while integrating seamlessly into the wall surface.
Constructed from durable die-cast aluminum with a protective finish, providing excellent strength and corrosion resistance for long-lasting performance.
Toughened glass and a durable sealing system provide reliable protection for both indoor and outdoor applications.
Fully recessed installation keeps the luminaire discreet and flush with the wall, minimizing visual obstruction while enhancing architectural aesthetics.
Suitable for stairways, walkways, corridors, entrances, landscape pathways, terraces, hotels, residential areas, and commercial spaces.

Product Specifications:

Front cover : Die cast Aluminium
Housing : Die cast Aluminium
Coating : Powder Coating
Light Source: Osram / Cree
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 2.7W
Voltage: 220-240VAC
Frequency: 50-60Hz
Lumen: 26lm/W
Mac Adam: 3 Step
Safety Class: III
Cut Out : L72xW35xH70
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	2.7W
Finish	:	Grey (G) / Black (B) / White (W)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	90°
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI

*Lumen values are calculated at 90° beam angle, 4000K color temperature and CRI 80.

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539079	02 - 2.7W	27-2700K 30-3000K 40-4000K 60-6000K	A-220-240VAC	90 - 90°	G-Grey B-Black W-White	1-DALI


Ex: Order Code: 5390790227A'90G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539079	02 - 2.7W	27-2700K 30-3000K 40-4000K 60-6000K	A-220-240VAC	90 - 90°	G-Grey B-Black W-White	1-ON/OFF

Ex: Order Code: 5390790227A'90G1

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C