




DAWA



Features:

DAWA Architectural Light, is seamlessly blends modern design with cutting-edge technology, offering both elegance and high efficiency.

Equipped with a high-efficiency LED light source, it delivers bright, uniform illumination while consuming minimal power.

The light features a professional optical PC diffuser with low anti-glare value, providing a soft, comfortable light that creates a welcoming ambiance without straining the eyes, With constant current technology.

This pendant light ensures consistent, safe, and reliable performance over time. Its low power consumption further enhances its eco-friendly credentials, making it an ideal lighting solution for those seeking both sustainability and style.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 12-24W

High Lumen: 110lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: SMD2835 LED

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C

(L80/B10).

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Conference rooms

Counters

Restaurants

Installation Method:

Recessed

Wattage(W)	:	12	24		
Finish	:	White(W)			
Kelvin*	:	3000K	4000K	5000K	6500K
Beam Angle	:	360°			
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming


*Special Color and Finish on request

Product Code (96803824):

Wattage	Lumens(lm)	Dimension(Øx L) mm
12	1320LM	38X600
24	2640LM	38X1200

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96803824 30K 360D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	360D - 360°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	
50K - 5000K			3 - DALI	
65K - 6500K			4 - Phase Dimming	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C