


DROP



Features:

DROP Anti-glare cylinder Type LED Light, extrusion aluminum body.
 High efficiency aluminum reflector to ensure that the light is more soft and comfortable.
 Die-casting aluminum body with lens and radiator with good heat dissipation.
 Easy to install and maintain.
 Fast and simple screw lock type Metal ceiling base easy to install and maintain
 High light Transmissivity.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
 Wattage: 8 W
 High Lumen: 110lm/w
 3 STEP Mac Adam
 High efficiency, low flicker driver
 Lamp Type: COB
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail
 Education
 Galleries hotels
 Living spaces
 Conference rooms
 Counters
 Restaurants

Installation Method:

Suspended

Wattage(W)	8				
Finish	White(W)	Black(B)	Silver (S)		
Kelvin*	2700K	3000K	4000K	5000K	5700K
Beam Angle	15°	24°	36°		
CRI	80+	90+			
Driver	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


*Special Color & Finish on request

Product Code (96805008S):

Wattage	Lumens(lm)	Dimension(ØxH) mm
8	880LM	50x180

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Standards

- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96805008S 27K 15D & 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	36D - 36°		3 - DALI	S-Silver
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C