


ECHO



Features:

ECHO Is Grid Adjustable Magnetic track light installed on Low Voltage Magnetic Track . Typically refers to refers to the aesthetic or functional design of the fixture's housing, that means a structured on the surface, and aids in heat dissipation and light diffusion.

It is made of aluminum body with PMMA lens.

The die cast aluminum body offers excellent thermal conductivity, which helps in dissipating heat generated by the LED chip.

At the same time, the low-voltage DC40V input scheme is adopted.

The magnetic track allows you to easily move and adjust the position of the light fixture along the track.

Technical Specifications:

- Input Voltage: 40V DC, 50 Hz.
- Wattage: 16W
- High Lumen: 80lm/w
- 3 STEP Mac Adam
- High efficiency, low flicker driver
- Lamp Type: SMD Module
- Operating Temperature: -20°C to 45°C
- Glow Wire Test 850° C
- Warranty: 5 Years
- Life Time: 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

- Retail
- Education
- Galleries hotels
- Living spaces

Installation Method:

On an electrified Magnetic track 40V DC

Wattage(W)	:	16				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	60°				
CRI	:	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


*Special Color and Finish on request

Product Code (76533016.03):

Wattage	Lumens(lm)	Dimension(LxWxH) mm
16	1280LM	330x25x64

*Luminous lux value is calculated for 4000K CRI>90

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: ~~76533016.03~~ 27K 60D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	60D - 60°	9->90	1 - ON/OFF	W-White
30K - 3000K			2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C