


ELOY



Features:

ELOY is recessed downlight, die cast aluminum body with stable heat dissipation and more durable.

High reflectance aluminum reflector for extend long service lifetime.

Uniform spot transition without residual light.

Homogenous, well-balanced light dispersing, no shadow

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 40 W

High Lumen: 110lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail

Galleries hotels

Living spaces

Conference rooms

Counters

Restaurants

Installation Method:

Fixed Recessed.

Wattage(W)	:	40				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	70°				
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


*Special Color & Finish on request

Product Code (98822040):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out (mm)
40	4400LM	220x120	190

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 98822040 27K 70D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	70D - 70°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C