
pluxb

IP65 IK08

EMMY





Description:

EMMY is a Compact and slim design, up and down wall light, adjustable slides integrated. Wall-mounted corner lights combines innovative design with energy-efficient features. Crafted from die-cast aluminum with high corrosion resistance, the fixture ensures long-lasting durability. Whether you're lighting up your garden, patio or porch, it provides bright, reliable light while enhancing the aesthetic appeal of your space.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Gasket: Moulding shaped silicone seal
Light Source: OSRAM / CREE
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface mounted
Adjustable: No

Technical Specifications:

Wattage: 6 - 9W
Voltage: 220-240VAC
Frequency: 50-60Hz
Lumen: 35lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	6W / 9W
Finish	:	Black (B) / White (W) / Grey (G) / Brown (BR)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	120°
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540182	06 - 6W (2x3W) 09 - 9W (2x4.5W)	27-2700K 30-3000K 40-4000K 60-6000K	A-220-240VAC	120 - 120°	B - Black W - White G- Grey BR- Brown	1-ON/OFF 2-DALI

Ex: Order Code: 5401820627A'120B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C