



EOLA



CUT OUT 35



40



Features:

EOLA A recessed downlight with a modern and minimal design, seamlessly integrated into the ceiling to provide a clean and elegant lighting effect. This lighting fixture is designed to deliver focused and efficient illumination while maintaining a sleek architectural appearance. The soft and comfortable light output makes it suitable for spaces that require long-hour illumination without glare or flicker. The high-quality aluminum body ensures excellent durability and efficient heat dissipation. Aluminum is lightweight yet strong, helping maintain the structural stability of the fixture while preventing overheating. The fixture structure ensures UGR < 3, delivering comfortable, glare-controlled lighting. It also provides strong resistance to wear and long-term use. The PC lens with chrome reflector evenly diffuses the light, reducing glare and creating soft, comfortable illumination. It is also highly resistant to UV rays, ensuring long-lasting clarity and consistent lighting performance over time.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.
 Wattage: 4W
 High Lumen: 80lm/w
 3 STEP Mac Adam
 High efficiency, low flicker driver
 Lamp Type: COB
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail
 Education
 Galleries hotels
 Living spaces
 offices
 hospitals

Installation Method:

Recessed Adjustable

Wattage(W)	:	4				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5700K
Beam Angle	:	21°	24°	44°		
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	

*Special Color & Finish on request




Product Code (97704004.50):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out  (mm)
4	320LM	40x66	35

*Luminous flux value is calculated for 4000K CRI>90

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 97704004.50 27K 21D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	21D - 21°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	44D - 44°		3 - DALI	
40K - 4000K			4 - Phase Dimming	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C