











ESSENCE I


























Features:

ESSENCE I is high quality edge lit panel, Ultra slim design. It constructed using aluminium frame body and non-yellowing opal diffuser.

It can be mounted in ceiling recessed, surface mounted and suspended as per requirement.

Uniform light distribution, Optimum glare control, Passive cooling, Homogeneous light output in low depth of housing, No infrared rays, No ultraviolet radiation.

Lighting sensors and Motion sensors are optional.

Technical Specifications:

Input Voltage: 220-240V AC, 50 Hz.

Wattage: 20-40W High Efficacy: 130lm/w 3 STEP Mac Adam

High efficiency, low Flicker driver

UGR >19

Operating Temperature: -20°C to 50°C

Glow Wire Test 850° C Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

School Offices lobbies Hallway Hospital Restaurants Meeting Rooms

Installation Method:

Box Surface Mounted / Recessed

| Wattage(W) | : 20 | 25 | 35 | 40 | | |
|------------|--------|----------|-----------|------------|---------|-----------|
| Finish | : Whit | e(W) | Silver(S) | | | |
| Kelvin* | : 3000 |)K 40 | 00K 5 | 5700K | 6500K | |
| Beam Angle | : 90° | 120° | | | | |
| CRI | : 80+ | | | | | |
| Driver | : ON/0 | OFF 0/1- | 10V DAL | .I Phase D | Dimming | Bluetooth |

*Special Color & Finish on request

Product Code (967119540):

| Wattage | Lumens(Im) | Dimension(LxWx H) mm |
|---------|------------|----------------------|
| 20 | 2,600LM | 1195x295x10 |
| 25 | 3,250LM | 1195x295x10 |
| 35 | 4,550LM | 1195x295x10 |
| 40 | 5,200LM | 1195x295x10 |

^{*}Luminous flux value is calculated for 4000K CRI>80

Photometric:





Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

Order Code Ex: 967119540 30K 90D 8 CCT Beam Angle CRI Driver **Finish** 1-ON/OF 2-0/1-10 3-DAL 4-Phase Dimming

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



LED PANEL LIGHT

INSTALLATION



ACCESSORIES LIST

