

EUNA



Description:

EUNA is a compact wall-mounted light fixture with LED elements. The LEDs are encased in a sleek, protective housing with a bracket for secure mounting.

This design is likely intended for both indoor and outdoor applications, offering efficient and focused illumination while being protected from environmental factors. The sturdy construction suggests durability and reliability in various settings.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Dimension : 110*50mm

Product Specifications:

Front cover : Die cast Aluminium grey
 Housing : Die cast Aluminium grey
 Diffuser : Glass lenses
 Gasket: Moulding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface mounted
 Adjustable: No

Technical Specifications:

Wattage: 4 - 6W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Year

Parameter:


Wattage(W)	:	4W / 6W
Finish	:	Grey (G) /Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	8° / 15° / 25° / 40° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540110	04-4W(2x2W)	27-2700K	A-220-240VAC	8-8°	G-Grey	1-ON/OFF
	06-6W(2X3W)	30-3000K		15-15°	C-Customized	2-DALI
		40-4000K		25-25°		3-0/1-10V
		60-6000K		40-40°		4-Phase cut
				60-60°		

Ex: Order Code: 5401100427A'8G1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C