


EVA PRO



Features:

Eva Pro Trimless Recessed downlight with highly efficacy PC reflector and PMMA lens.
 Precision engineered adjustment mechanism, easy to adjust to specific angle.
 Thermally engineered heatsink creates highly efficient passive cooling system.
 Different colors of secondary reflector are available.
 Anti-glare accessory provides maximum eye comfort.
 30° tilt and 355° rotation.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
 Wattage: 2X10 - 2X15 W
 High Lumen: 115lm/w
 3 STEP Mac Adam
 High efficiency, low flicker driver
 Lamp Type: COB
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850°C
 Warranty: 5 Years
 Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail
 Galleries hotels
 Living spaces
 Conference rooms
 Counters
 Restaurants

Installation Method:

Trimless Recessed Adjustable

Wattage(W)	:	2X10	2X15		
Finish	:	White(W)	Black(B)	Gray(G)	
Kelvin*	:	2700K	3000K	4000K	5000K 5700K
Beam Angle	:	15°	24°	36°	
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming Bluetooth


*Special Color & Finish on request

Product Code (96814130.40):

Wattage	Lumens(lm)	Dimension(LxW xH) mm	Cut out ⌀ (mm)
2X10	2300LM	141.5x154.4x99	141.5x72
2X15	3450LM	141.5x154.4x109	141.5x72

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96814130.40 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	36D - 36°		3 - DALI	G-Gray
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C