


EVAPRO



Secondary Reflector



Features:

- Eva Pro Trimless Recessed downlight with highly efficacy PC reflector and PMMA lens.
- Precession engineered adjustment mechanism, easy to adjust to specific angle.
- Thermally engineered heatsink creates highly efficient passive cooling system.
- Different colors of secondary reflector are available.
- Anti-glare accessory provides maximum eye comfort.
- 30° tilt and 355° rotation.

Technical Specifications:

- Input Voltage: 220-240 V AC, 50 Hz.
- Wattage: 20 - 25 W
- High Lumen: 115lm/w
- 3 STEP Mac Adam
- High efficiency, low flicker driver
- Lamp Type: COB
- Operating Temperature: -20°C to 45°C
- Glow Wire Test 850° C
- Warranty: 5 Years
- Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

- Retail
- Galleries hotels
- Living spaces
- Conference rooms
- Counters
- Restaurants

Installation Method:

- Recessed Adjustable

| | | | | | |
|------------|---|----------|----------|---------|-------------------------|
| Wattage(W) | : | 20 | 25 | | |
| Finish | : | White(W) | Black(B) | Gray(G) | |
| Kelvin* | : | 2700K | 3000K | 4000K | 5000K 5700K |
| Beam Angle | : | 15° | 24° | 36° | |
| CRI | : | 80+ | 90+ | | |
| Driver | : | ON/OFF | 0/1-10V | DALI | Phase Dimming Bluetooth |


*Special Color & Finish on request

Product Code (96814725.20):

| Wattage | Lumens(lm) | Dimension(LxØx H) mm | Cut out ⌀ (mm) |
|---------|------------|----------------------|----------------|
| 20 | 2300LM | 147x92.5x109.5 | 95 |
| 25 | 2875LM | 147x92.5x121.5 | 95 |

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96814725.20 27K 15D 8 1 W

| CCT | Beam Angle | CRI | Driver | Finish |
|-------------|------------|-------|-------------------|---------|
| 27K - 2700K | 15D - 15° | 8->80 | 1 - ON/OFF | W-White |
| 30K - 3000K | 24D - 24° | 9->90 | 2 - 0/1-10V | B-Black |
| 40K - 4000K | 36D - 36° | | 3 - DALI | G-Gray |
| 50K - 5000K | | | 4 - Phase Dimming | |
| 57K - 5700K | | | 5 - Bluetooth | |

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C