



## EYE



### Description:

EYE round wall light, typically small circular fixture designed for outdoor or indoor use. It is installed flush with a surface, such as a stair, deck, or pathway, to provide illumination and enhance safety.

These lights often have a low profile, durable construction, and are designed to withstand various weather conditions.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

Round step lights are commonly used to illuminate steps, walkways, or other areas where low-level, subtle lighting is desired for both aesthetic and practical purposes.

### Product Specifications:

Front cover : Die cast Aluminum grey  
 Housing : Die cast Aluminum grey  
 Glass : NA  
 Gasket: Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Wall Mounted  
 Adjustable: No

### Technical Specifications:

Wattage: 1 - 1.5W  
 Voltage: 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: II  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

### Parameter:


Wattage(W)	:	1W / 1.5W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	80°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540042	02-1W(1x1W)	27-2700K	A-220-240VAC	80-80°	G-Grey	1-ON/OFF
	02-1.5W(1x1.5W)	30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				4-Phase cut

**Ex: Order Code:** 5400420227A'80G1

### Photometric:



### Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C