


EYE



Description:

EYE round wall light, typically small circular fixture designed for outdoor or indoor use. It is installed flush with a surface, such as a stair, deck, or pathway, to provide illumination and enhance safety.

These lights often have a low profile, durable construction, and are designed to withstand various weather conditions.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

Round step lights are commonly used to illuminate steps, walkways, or other areas where low-level, subtle lighting is desired for both aesthetic and practical purposes.

Product Specifications:

Front cover : Die cast Aluminum grey
 Housing : Die cast Aluminum grey
 Glass : NA
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Wall Mounted
 Adjustable: No

Technical Specifications:

Wattage: 5W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:


Wattage(W)	:	5W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	80°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540070	05-5W(1x5W)	27-2700K	A-220-240VAC	80-80°	G-Grey	1-ON/OFF
		30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				4-Phase cut

Ex: Order Code: 5400700527A'80G1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C