


## FENCE'S



### Description:

FENCE'S is a modern decorative wall-mounted LED light fixture with a minimalist, rectangular design. The light source is positioned at the downward and upward direction. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.

These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

### Product Specifications:

Housing : Die cast Aluminium  
Diffuser : Tempered Glass  
Gasket: Moulding shaped silicone seal  
Power Cable: 0.5 mt. power cable  
Driver : High efficiency, low flicker driver  
Installation Type: Wall Mounted  
Adjustable: No  
Warranty: 5 Years

### Technical Specifications:

Wattage: 6W  
Voltage: 85-265VAC, 50-60Hz  
Light Source: OSRAM/ EPISTAR/ CREE  
Lumen: 100lm/W  
Mac Adam: 3 Step  
Safety Class: II  
Working Temperature:-20°C to 55°C  
Life Time: 50,000hrs (L80/B10) at 35°C

### Parameter:


Wattage(W)	:	2x3W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540115	06-6W(2x3W)	27-2700K	A-220-240VAC	120-120°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	3-0/1-10V
		60-6000K			C-Customized	

**Ex: Order Code:** 5401150627A120G1

### Photometric:



### Standards :

EN 60598-1  
EN 60598-2-2  
EN 60598-3-2  
EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C