


FLASH



Description:

FLASH is a Linear inground outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination. These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas.

Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions

It comes with different CCT, R/G/B LED sources and various beam angles this family is a perfect solution to the requirement.

They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

Front cover : Stainless steel 316 SUS
 Housing : Die cast Aluminum grey
 Glass : Tempered Clear glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Inground
 Adjustable: No

Technical Specifications:

Wattage: 6 - 9W
 Voltage: DC24V / 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: III / II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	: 6W / 9W
Finish	: Stainless Steel 316 SUS (SS)
Kelvin*	: 2700K/ 3000K/ 4000K/ 6000K/ RGB
Beam Angle	: 10° / 25° / 30° / 45° / 60°
CRI	: 80
Control Mode	: ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX


Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5496361	06-6W(3X2W)	27-2700K	D-24VDC	10-10°	SS-Stainless Steel 316	1-ON/OFF
	09-9W(3X3W)	30-3000K		25-25°		2-DALI
		40-4000K		30-30°		3-0/1-10V
		60-6000K		45-45°		4-Phase cut
		92-RGB		60-60°		5-DMX
		93-RGB DMX				

Ex: Order Code: 1

54963610627D'10SS

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5496361	06-6W(3X2W)	27-2700K	A-220-240VAC	10-10°	SS-Stainless Steel 316	1-ON/OFF
		30-3000K		25-25°		2-DALI
		40-4000K		45-45°		3-0/1-10V
		60-6000K		60-60°		4-Phase cut
						5-DMX

Ex: Order Code: 54963610627A'10SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C