


## GAVEL'F

**Description:**

GAVEL'F is a Linear inground outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination.

These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas.

Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions

It comes with different CCT, R/G/B LED sources and various beam angles this family is a perfect solution to the requirement.

They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

**Product Specifications:**

Front cover : Stainless steel 316 SUS  
 Housing : Die cast Aluminum grey  
 Glass : Matt glass  
 Gasket: Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Inground  
 Adjustable: No

**Technical Specifications:**

Wattage: 20 - 25W  
 Voltage: DC24V / 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: III / II  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

**Parameter:**

|              |   |   |
|--------------|---|---|
| Wattage(W)   | : | 20W / 25W                                   |
| Finish       | : | Stainless Steel SUS 316 (SS)                |
| Kelvin*      | : | 2700K/ 3000K/ 4000K/ 6000K/ RGB /RGBW       |
| Beam Angle   | : | 120°  |
| CRI          | : | 80  |
| Control Mode | : | ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX |

**Order Code:**

| Product Code | Wattage         | CCT         | Voltage | Beam Angle | Finish                 | Control Mode |
|--------------|-----------------|-------------|---------|------------|------------------------|--------------|
| 5497586      | 20-20W(36X0.5W) | 27-2700K    | D-24VDC | 120-120°   | SS-Stainless Steel 316 | 1-ON/OFF     |
|              | 25-25W(36X0.7W) | 30-3000K    |         |            |                        | 2-DALI       |
|              |                 | 40-4000K    |         |            |                        | 3-0/1-10V    |
|              |                 | 60-6000K    |         |            |                        | 4-Phase cut  |
|              |                 | 92-RGB      |         |            |                        | 5-DMX        |
|              |                 | 93-RGB DMX  |         |            |                        |              |
|              |                 | 92-RGBW     |         |            |                        |              |
|              |                 | 93-RGBW DMX |         |            |                        |              |

54975862027D'120S

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

| Product Code | Wattage         | CCT      | Voltage      | Beam Angle | Finish             | Control Mode       |
|--------------|-----------------|----------|--------------|------------|--------------------|--------------------|
| 5497586      | 20-20W(36X0.5W) | 27-2700K | A-220-240VAC | 120-120°   | SS-Stainless Steel | 3161-ON/OFF        |
|              |                 | 30-3000K |              |            |                    | 2-DALI             |
|              |                 | 40-4000K |              |            |                    | 3-0/1-10V          |
|              |                 | 60-6000K |              |            |                    | 4-Phase cut        |
|              |                 |          |              |            |                    | 5-DMX              |
|              |                 |          |              |            |                    | 54975862027A'120S  |
|              |                 |          |              |            |                    | Ex: Order Code: S1 |

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C