



GLAZ



Features:

GLAZ Adjustable track light for installation on mains voltage track.

High quality die cast aluminum body, Cold forging process on high purity metal, which have good heat dissipation and strengthen the housing surface, make precise and good quality product.

Alanood reflectors for long-term stability of reflector surfaces and tested under toughest conditions, even after 50,000hours, our surfaces made of MIRO and MIRO-SILVER showed unchanged, high reflection properties.

Universal line voltage led track lighting heads, fit in 2 wires, 4 wires, 6 wires Track systems.

Adjustable Angle with 355° horizontal rotation, 90° vertical adjustment.

More accurate and professional multi-angle lighting beams.

Accurate and efficient light control, triple anti-glare led track spot light.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 15-36W

High Lumen: 130lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

On an electrified track or special base.

Wattage(W)	:	15	20	25	30	36
Finish	:	White(W)	Black(B)	Gray(G)	Customized	
Kelvin*	:	2700K	3000K	3500K	4000K	5000K 5700K
Beam Angle	:	15°	24°	45°	60°	
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth





*Special Color and Finish on request

Product Code (96509036):

Wattage	Lumens(lm)	Dimension(Ø x L) mm
15	1950LM	90x130
20	2600LM	90x130
25	3250LM	90x130
30	3900LM	90x130
36	4680LM	90x130

*Luminous Lux value is calculated for 4000K and CRI>90

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96509036 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	45D - 45°		3 - DALI	G-Gray
40K - 4000K	60D - 60°		4 - Phase Dimming	C-Customized
50K - 5000K			5 - Bluetooth	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C